

PRODUCT

FV-PRO IPC9433E2 - 3 Megapixel Real Time External IP Bullet Style Camera

1080P Variable Real Time Encoding. Dual Stream Bullet Style. ICR auto switch for Day/Night functions. 42 IR LED's for 40m + night vision. One Way Audio. 12V DC or POE.



DETAILS

1080P Variable Real Time Encoding. Dual Stream Bullet Style. ICR auto switch for Day/Night functions. 40 IR LED's for 40m + night vision. One Way Audio. 12V DC or POE..

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
AGC/Digital Sense up	-
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	-
BLC/SSDR (WDR)	Digital WDR
Communication System	-
Connection Cable	DC + POE / Video / Audio (RJ45)
Control Capability	-
DNR	3D
Dimensions	Length 326mm - Diameter - 112mm
Dual Streaming	Yes
Effective Pixel	2048 (H) x 1536 (V)
Enhancement	Yes
Gamma Correction	0.45

Horizontal Resolution	1000TVL
IR Illumination	42pc Array LED
Image Sensor (CCD)	3 Megapixel
Joystick Control	-
LCD Screen	-
Lens	2.8~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens (Optical)	2.8~12mm Megapixel Day / Night Lens
Lens Facilities	-
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	0 Lux with IR LED's on
Model	3 Megapixel - 2.8~12mm Varifoal lens, True Day Night Dual Stream 12V DC or POE & Dual Stream
Multiple Present Sequencing	-
POE	Yes
Power Consumption	-
Power Source	12V DC Regulated or POE
Presets	-
Privacy	Yes
RS485 Interface	-
S/N Ratio	52db +
Scanning System	PAL
Shutter	Yes
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP and BNC
Weight(Cameras)	1kg
Within Range of IR LEDs	40m