

PRODUCT



FV-PRO IPC9525S2 - 2MP IP Eyeball IR Dome.WDR NR.
2.8~12mm Varifocal. POE

2MP (1920 × 1080) H.265 full real time coding

Max. resolution: 1920 × 1080; ICR auto switch, true day / night

30 ~ 50m IR night view distance

3D DNR, Digital WDR, HLC, BLC and Defog

ROI coding

Hardware reset

Built-in micro SD card slot, up to 128GB

DC12V/PoE power supply

IP67 ingress protection

Supports dual streams

Support mobile surveillance by smart phones with iOS and
Android OS

DETAILS

ADDITIONAL INFORMATION

AGC	Auto
Accessories Available	Yes
Aperture Correction	H aperture V aperture
BLC/SSDR (WDR)	Digital WDR
Connection Cable	DC + POE / Video / Audio (RJ45)
DNR	3D
Dimensions	Width - 119mm - Height - 96mm
Dual Streaming	Yes
Effective Pixel	1920(H) x 1080(V)
Gamma Correction	0.45
Horizontal Resolution	1000TVL
IR Illumination	Array LED
Image Sensor (CCD)	2 Megapixel
Lens	2.8~12mm Megapixel Day / Night Lens
Lens (Optical)	2.8~12mm
Minimum Illumination - Colour	0.005 lux@F1.6, AGC ON; 0 lux with IR
Minimum Illumination - Mono	0 Lux with IR LED's on

Model	2 Megapixel - 2.8~12mm Varifocal lens, True Day Night, Audio, Dual Stream 12V DC or POE & Dual Stream
Power Source	12V DC Regulated or POE
S/N Ratio	52db +
Scanning System	PAL
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Weight(Cameras)	700g
Within Range of IR LEDs	30-50m