

## PRODUCT

FV-PRO IPC9545E2 - 4 Megapixel Real Time External 3.3-12mm Eyeball Dome Camera with array LED's.

4MP H265 / H264 Max.resolution: 2592x1520 ICR auto switch,true day/night 30m IR night view distance Electric zoom optional 3D DNR,digital WDR ROI coding Supports local CVBS video output. Supports POE power supply smart phone, IPad, remote monitoring P2P Triple stream



## DETAILS

4MP H265 / H264 IP Infrared Eyeball Dome camera. Array type LED's. 3.3-12mm Varifocal Lens

## ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
AGC/Digital Sense up	-
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	-
BLC/SSDR (WDR)	Digital WDR
Communication System	-
Connection Cable	DC + POE / Video / Audio (RJ45)
Control Capability	-
DNR	3D
Dimensions	Width 109mm - Height - 130mm
Dual Streaming	Yes
Effective Pixel	2592 x 1520
Enhancement	-
Gamma Correction	0.45
Horizontal Resolution	1000TVL

IR Illumination	2 Array LED's
Image Sensor (CCD)	1/3" CMOS 4MP
Joystick Control	-
LCD Screen	-
Lens	3.3~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens (Optical)	3.3~12mm Megapixel Day / Night Lens
Lens Facilities	-
Lens Mount	-
Minimum Illumination - Colour	0.05lux@F1.2, AGC ON
Minimum Illumination - Mono	0 Lux with IR LED's on
Model	IPC9545 - 4MP 3.3-12mm Eyeball Dome
Multiple Present Sequencing	-
POE	Yes
Power Consumption	~7W
Power Source	12V DC Regulated or POE
Presets	-
Privacy	-
RS485 Interface	Yes
S/N Ratio	52db +
Scanning System	PAL
Shutter	1/25s ~ 1/100000s
Sync System	2:1 Internal
Sync. Type	-
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	-
Weight(Cameras)	1kg
Within Range of IR LEDs	30m