


PRODUCT

Dynacolor SL4H264TX - PRO-1 - 960H 4 Channel SILENT H264 Pentaplex DVD+RW USB Webserver

Key Features:

- Optimised H264 Compression.
- Internal Hard Drive capacity up to 6TB.
- DVD+RW.
- Main Monitor Output; from BNC Composite, VGA or HDMI + BNC Call (Spot) Monitor.
- Camera Lopp Outputs.
- Single, Sequential or Quad Camera Split Screen Display.
- EZRecord for the fastest setup.
- 2 USB-2 Ports for fast download to a USB Memory stick using EZBurn.
- Webserver for Fast Network and Remote Internet or Smartphone viewing.
- 10000 Event Motion Detection and Alarm Inputs.
- Covert Mode.
- Playback by Time & Date.
- Event List Playback.
- Dome Control.
- USB Mouse Control from USB-2 port.
- IR Remote included.
- Optional D7324 RS485 IR Extender and DVR Keyboard D7323 or DVR & PTZ D7313H Joystick Keyboard.



DETAILS

4ch High Resolution 960H Real Time DVR Range with DVD-RW, USB, Webserver for Network and Remote Internet or Phone access.

ADDITIONAL INFORMATION

Accessories Included	IR Remote
Accessories Optional	D7324 IR Extender + D7323 DVR & D7313H PTZ + DVR RS485 Keyboards
Alarm Inputs / Relay Outputs	4 / 1
Alarm Notification	Yes, via email
Alarm Recording	Yes
Audio Inputs	4
Backup Device	DVD and USB
Broadband Internet Access	Yes - Webserver with Router - no software needed
Call Monitor Output	BNC, VGA & HDMI
Camera Input	4
Camera Loop Out	4
Compression Method	H264HR (optimised)
Device Expansion	No

Dimensions	436(W) x 85(H) x 380(D)mm
Dome & PTZ Controls	Yes
Event Backup	DVD & USB
Event List	Event list playback
Hard Drive Options	1TB / 2TB / 3TB./ 4TB / 6TB
Image Quality	18 Combinations from Best to Fast Transmission
Image Record Rate	up to 100 PPS
Main Monitor Output	1 BNC Composite Video + VGA + HDMI
Model	SL4H264TX-960H Full Function Real Time DVR with DVD+RW / USBx3 and Webserver
Motion Detection	Yes - 10000 Event List
NET Weight	4.7kgs
Network Access (LAN)	Yes - Webserver
Password Control	Yes
Playback Speed	up to 32x
Power	AC100~240V
Record Facilities	Pentaplex + - Recording continues whilst operating any other function eg - Playback, Remote Access, DVD, USB etc.
Record Frame Rate (PPS)	Variable for each camera between 1, 3.12, 6.25, 9.35, 12.5 and 25 with maximum of 100 PPS
Recording Modules	Schedule / Manual / Alarm / Motion Detect
Recording Resolution (Quality Settings)	960H, D1, 2CIF and CIF modes
Relay Outputs	1
Remote Interface	RS485
Storage Media & Capacity	2 Internal HDD's - 1TB, 2TB, 3TB. 4TB. 6TB
Time and Date	Yes
Transmission / Networking	Inbuilt Full Web Server for internet and Networking. CMS Central Station multi DVR software available & JAVA software for MAC / Firefox
VGA Monitor Output	1 Standard D-Sub Socket
Zoom	Yes