

PRODUCT



FV-PRO AH2000 - 2 Megapixel 3.6mm Chrome Designer Style External or Internal Surface or Flush Mount Mini Dome

FV-PRO AH2000AM 2 Megapixel 3.6mm Chrome Designer Style External or Internal Surface or Flush Mount Mini Dome. True Day / Night. 3D DNR. Defog. D-WDR. 12V DC.

DETAILS

FV-PRO AH2000AM 2 Megapixel 3.6mm Chrome Designer Style External or Internal Surface or Flush Mount Mini Dome. True Day / Night. 3D DNR. Defog. D-WDR. 12V DC. .

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
AGC/Digital Sense up	-
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	-
Connection Cable	DC
Control Capability	-
DNR	3D
Dimensions	Width - 21mm - Length - 79mm
Dual Streaming	Yes
Effective Pixel	1920(H) x 1080(V)
Enhancement	-
Gamma Correction	0.45

Horizontal Resolution	1000TVL
IR Illumination	-
Image Sensor (CCD)	2+ Megapixel
Joystick Control	-
LCD Screen	-
Lens	3.6mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens (Optical)	3.6mm
Lens Facilities	-
Lens Mount	-
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	-
Model	FV-PRO AH2000AM 2 Megapixel 3.6mm Chrome Designer Style External or Internal Surface or Flush Mount Mini Dome
Multiple Present Sequencing	-
POE	-
Power Consumption	-
Power Source	12V DC Regulated
Presets	-
Privacy	-
RS485 Interface	-
S/N Ratio	>52db +
Scanning System	PAL
Shutter	1/50s~1/50000s
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	BNC
Weight(Cameras)	-
Within Range of IR LEDs	-