

PRODUCT

FV-PRO AH5500A-IR 2 Megapixel 2.8-12mm External Eyeball Dome Style Camera- Colour White or dark Grey

1080P 2 MPX 1000TVL Eyeball Style Dome with ICR for auto switch Day/Night functions. 3D DNR. Defog. D-WDR. 3 High Powered IR LED's for 35m night vision + Smart IR and Mirror Image. Motion Detection. 12V DC. Colour White or dark Grey.



DETAILS

1080P Variable Real Time Encoding. Dual Stream Eyeball Style. ICR auto switch for Day/Night functions. Defog. D-WDR. 3 High Powered IR LED's for 35m night vision + Smart IR and Mirror Image. Motion Detection. 12V DC. Colour White or dark Grey.

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
AGC/Digital Sense up	-
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	-
Connection Cable	DC + POE / Video / Audio (RJ45)
Control Capability	-
DNR	3D
Dimensions	Base Width - 115mm Height - 80mm
Dual Streaming	Yes
Effective Pixel	1920(H) x 1080(V)
Enhancement	-
Gamma Correction	0.45

Horizontal Resolution	1000TVL
IR Illumination	3pc High Powered IR LEDs
Image Sensor (CCD)	2+ Megapixel
Joystick Control	-
LCD Screen	-
Lens	2.8~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens (Optical)	2.8~12mm
Lens Facilities	-
Lens Mount	-
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	0 Lux with IR LED's on + Smart IR
Model	FV-PRO AH5500A-IR 2 Megapixel 2.8-12mm External Eyeball Dome Style Camera -Colour White or dark Grey
Multiple Present Sequencing	-
POE	-
Power Consumption	-
Power Source	12V DC Regulated
Presets	-
Privacy	-
RS485 Interface	-
S/N Ratio	>52db +
Scanning System	PAL
Shutter	1/50s~1/50000s
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	BNC
Weight(Cameras)	700g
Within Range of IR LEDs	30m