

## PRODUCT

FV-PRO 9433M2 - 3 Megapixel H.265 STARVIS Real Time Varifocal 2.8~12mm External IP Bullet Style Camera

H265 3 Megapixel STARVIS Varifocal 2.8~12mm Megapixel Varifocal lens, True Day Night Triple Stream 12V DC or POE. 2 Way Audio. 12V DC or POE.



## DETAILS

H265 3 Megapixel STARVIS Varifocal 2.8~12mm Megapixel Varifocal lens, True Day Night Triple Stream 12V DC or POE. 2 Way Audio. 12V DC or POE.

## ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
AGC/Digital Sense up	Auto
Aperture Correction	H aperture V aperture
Audio Inputs	2 Way Audio
BLC/SSDR (WDR)	Digital WDR
Connection Cable	DC + POE / Video / 2-way Audio (RJ45)
DNR	2D & 3D
Dimensions	Length 284mm - Diameter - 109mm
Dual Streaming	Yes
Effective Pixel	2048 (H) x 1536 (V)
Enhancement	Yes
Gamma Correction	0.45
Image Sensor (CCD)	3MP 1/3"
Lens	Varifocal 2.8~12mm Megapixel Day / Night Lens
Minimum Illumination - Colour	0.01
Minimum Illumination - Mono	0 Lux with IR LED's on

Model	IPC9433M2
POE	Yes
Power Source	12V DC Regulated or POE
Privacy	Yes
S/N Ratio	55db+
Scanning System	PAL
Shutter	Yes
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP and BNC
Within Range of IR LEDs	50m