

## PRODUCT

### FV-PRO DVR2716PRO - 5MP Hybrid 16 Channel P2P Pentaplex DVR



Supports 16ch 5MPX AHD,TVI Cameras, 1080P AHD,TVI & CVI Cameras + 4 FV-PRO IP Camera. Intuitive and user-friendly Graphic User Interface(GUI), Windows style, operation by Mouse Remote control via IE or CMS: Preview, Playback, Backup, PTZ and Configuration Multi-Mode Recording: Manual, Timer, Motion or Sensor Simultaneous 8CH Playback: Search: Time / Calendar / Events (alarm, motion) . Express and flexible backup via USB. Pentaplex for Live Viewing, Record, Playback, Backup and Remote operation simultaneously DHCP, DDNS, PPPoE Network protocol, IE browser and CMS P2P Cloud for Remote Access with no router setup needed. Dual Stream Technology.. Supports 10 users online simultaneously. BNC Spot and Call Output. VGA 1080P Output. HDMI 1080P Output. Supports up to 12TB. Powerful smart phone surveillance supporting Android and iPhone. Compatible with 3G Complete SDK function, easy to integrate with other applications

## DETAILS

The 2716-PRO is a Midi size Hybrid DVR that adopts the most advanced SOC technique to ensure 5MP High Definition recording on each channel. This DVR accepts 16 5MP Hybrid Cameras and/or 1080p Hybrid Cameras and/or Standard CVBS Analogue Cameras plus 4 IP Camera. No router setup required through P2P or standard IP setup for Remote, Network or Smartphone viewing, 4K/HDMI, VGA plus BNC Call / Spot monitor.

## ADDITIONAL INFORMATION

Accessories Included	IR Remote + Mouse
Accessories Optional	Yes
Alarm Inputs / Relay Outputs	4 / 1
Alarm Notification	Yes
Alarm Recording	Yes
Audio Inputs	4
Backup Device	USB x 2
Broadband Internet Access	Yes - Webserver with P2P Cloud - no Router Setup needed
Call Monitor Output	BNC
Camera Input	16 on BNC + 4 IP Cameras through a router
Camera Loop Out	No
Compression Method	H264 (Optimised)
Device Expansion	No
Dimensions	380×268×52 (W×D×H)
Dome & PTZ Controls	Yes
Dual Streaming	Yes

Event Backup	USB
Event List	Yes
Hard Drive Options	1TB / 2TB \ 3TB \ 4TB \ 6TB \ 8TB \ 12TB
Image Quality	5 Options of Picture KB Size
Image Record Rate	5MP at 10FPS
Main Monitor Output	1 HDMI, 1 VGA, 1 BNC
Model	FV-PRO 2716-PRO 16ch P2P Pentaplex 5MP Hybrid DVR
Motion Detection	Yes
NET Weight	3KG
Network Access (LAN)	Yes
POE	No
Password Control	Yes
Playback Speed	up to x32
Power	DC12V from AC100-240V Adaptor
Privacy	Yes
RS485 Interface	Yes
Record Facilities	24hr / Scedule / Motion / Alarm
Record Frame Rate (PPS)	Up tpo 400
Recording Resolution (Quality Settings)	5 Levels
Relay Outputs	1
Remote Interface	RS485
Resolution (Best)	5MP
Storage Media & Capacity	Max 12TB
Tillscan	No
Time and Date	Yes
Transmission / Networking	IP or P2P for no router setup requirement using Cloud Server, Webserver - CMS
VGA Monitor Output	1 Standard D-Sub Socket + HDMI
Zoom	Yes