

PRODUCT



FV-PRO 9553E2A 5 Megapixel H.265 3.3-12mm
Motorised Real Time IR 3 Stream External Vandal
Resistant Dome Style Camera - Face Recognition

5 Megapixel Motorised High Tier H265 with H264 and MJPEG
compatible 3 streams.. Variable Real Time Encoding. Vandal
Style. True WDR. ICR auto switch for Day/Night functions. 30 IR
LED's for 25m + night vision. Two Way Audio. 12V DC or POE.

DETAILS

ADDITIONAL INFORMATION

AES	-
AGC	Auto
AGC/Digital Sense up	-
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	WDR
BLC/SSDR (WDR)	True WDR
Communication System	IP
Connection Cable	DC + POE / Video (RJ45) & (BNC), Audio in / out
Control Capability	-
DNR	3D
Dimensions	Width - 150mm - Height - 114mm
Dual Streaming	Yes + Triple Streaming
Enhancement	-
Gamma Correction	0.45
Horizontal Resolution	2592x1944
IR Illumination	30pc LED

Image Sensor (CCD)	5 Megapixel
Joystick Control	-
LCD Screen	-
Lens	3.3~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens (Optical)	3.3~12mm
Lens Facilities	Varifocal
Lens Mount	-
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	0 Lux with IR LED's on
Model	5 Megapixel - 3.3~12mm Varifocal lens, True WDR True Day Night, Vandal Resistant, Audio, Triple Stream 12V DC or POE.
POE	Yes
Power Consumption	2.5W or 5W with IR on
Power Source	12V DC Regulated or POE
S/N Ratio	52db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Weight(Cameras)	1kg
Within Range of IR LEDs	25m