

PRODUCT



IPC-9821E2 - 2MP Covert Board Camera Non-POE

2MP (1920 × 1080) full real time coding Max Resolution: 1920 × 1080

Supports H.265, H.264 and MJPEG encoding

Supports Micro SD card local image / video storage,

Alarm pre-recording

BLC, HLC, True WDR and image flip

Supports three streams

Supports corridor mode / defogging / digital image stabilization / privacy mask / scene mode setting

Support 8 ROI coding

DETAILS

ADDITIONAL INFORMATION

Audio Inputs	One built-in microphone
BLC	Yes
DNR	3D DNR
Dimensions	30 × 30 × 29.5
Image Record Rate	1080P (1 ~ 30fps) / 720P (1 ~ 30fps) / D1 (1 ~ 30fps)
Image Sensor (CCD)	1 / 3 "CMOS
Lens	4.3 mm HD pinhole lens
Minimum Illumination - Colour	0.1 Lux@F1.2;
Minimum Illumination - Mono	0.01 Lux@F1.2
Operating Temperature	- 20 °C ~ 50 °C, 10 % ~ 90 % humidity
POE	No. DC12V
Power Consumption	≤2W
Resolution (Best)	1080P (1920×1080), 720P (1280×720), D1
Shutter	1 / 25 s ~ 1 / 100000 s
Storage Media & Capacity	Up to 128GB Storage Card
Video Output Signal	1Vp-p Composite Output[] 75Ω/BNC[]
Weight(Cameras)	97g