

## PRODUCT



IPC-9821E2 - 2MP Covert Board Camera with Built-in Audio. Non-POE

2MP ( 1920 × 1080 ) full real time coding Max Resolution: 1920 × 1080

Supports H.265, H.264 and MJPEG encoding

Supports Micro SD card local image / video storage,

Alarm pre-recording

BLC, HLC, True WDR and image flip

Supports three streams

Supports corridor mode / defogging / digital image stabilization / privacy mask / scene mode setting

Support 8 ROI coding

## DETAILS

### ADDITIONAL INFORMATION

|                               |   |
|-------------------------------|---|
| Audio Inputs                  | One built-in microphone                                     |
| BLC                           | Yes   |
| DNR                           | 3D DNR  |
| Dimensions                    | 30 × 30 × 29.5  |
| Image Record Rate             | 1080P ( 1 ~ 30fps ) / 720P ( 1 ~ 30fps ) / D1 ( 1 ~ 30fps ) |
| Image Sensor (CCD)            | 1 / 3 "CMOS   |
| Lens                          | 4.3 mm HD pinhole lens                                      |
| Minimum Illumination - Colour | 0.1 Lux@F1.2;   |
| Minimum Illumination - Mono   | 0.01 Lux@F1.2   |
| Operating Temperature         | - 20 °C ~ 50 °C, 10 % ~ 90 % humidity                       |
| POE                           | No. DC12V   |
| Power Consumption             | ≤2W   |
| Resolution (Best)             | 1080P ( 1920×1080 ), 720P ( 1280×720 ), D1                  |
| Shutter                       | 1 / 25 s ~ 1 / 100000 s                                     |
| Storage Media & Capacity      | Up to 128GB Storage Card                                    |
| Video Output Signal           | 1Vp-p Composite Output[] 75Ω/BNC[]                          |
| Weight(Cameras)               | 97g   |