

PRODUCT



FV-PRO IPC9524S3A - 2MP IP Turret with Built-in Audio
Indoor/Outdoor with IR LED HD 2.8mm Wide Angle lens,
Multi Stream, POE

2MP (1920 × 1080) H.265

Built-in Audio

Max. resolution: 1920 × 1080

ICR auto switch, true day / night

20m IR night view distance

3D DNR, D-WDR, HLC, BLC, Smart IR and ROI coding

DC12V/PoE power supply

Support smart phone, iPad, remote monitoring

IP67 ingress protection

Support three streams

P2P function optional

Smart analytics (optional): abnormal video signal detection, line
crossing detection and region intrusion detection

DETAILS

ADDITIONAL INFORMATION

AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE
DNR	2D/3D DNR
Dimensions	Ø 94.6mm×82.8mm
Dual Streaming	Support three streams
Effective Pixel	3840 × 2160
Gamma Correction	0.45
Gross Weight	Approx. 0.45KG
IR Illumination	Up to 30m
Image Sensor (CCD)	1/2.5" 8 Megapixel

Lens	3.6 mm @F1.6, horizontal field of view: 87.7°
Minimum Illumination - Colour	0.024 lux @F1.2, AGC ON
Minimum Illumination - Mono	0 lux with IR
Model	IPC9524S2A
POE	Yes
Power Consumption	<6W
Power Source	12V DC Regulated or POE
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Within Range of IR LEDs	Up to 20m