

# PRODUCT



FV-PRO DVR2108-4K - 8MP 4K Lite Hybrid 8 Channel P2P Pentaplex DVR

8 CH TVI / AHD video input, support 8MP/5MP/4MP/3MP/1080P/720P/WD1

8 CH CVI video input, support 4MP / 3MP / 1080P / 720P / WD1

8 CH DVRs default support 8 CH IPC 8MP / 5MP / 4MP / 3MP / 1080P / 720P/WD1

Adopts standard H.265 high profile compression format to get high-quality video at much lower bit rate

Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse

Multi-mode recording: manual / timer / motion Playback : 8 CH simultaneously playback

Search: time slice, time, event ( manual, motion ), tag search Express and flexible backup via USB,network and so on Pentaplex: preview, record, playback, backup and remote access

DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported Remote control via IE or CMS : preview, playback, backup, PTZ and configuration

Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-user online simultaneously

Authorization management, log review and device status review HDMI 4K output, true high resolution display

Support PTZ preset and auto cruise, up to 255 presets and 8 cruises

Support NAT function and QRCode scanning by mobile phone and PAD

Powerful smart phone & Pad surveillance with iOS and Andriod OS

## DETAILS

### ADDITIONAL INFORMATION

Accessories Included	IR Remote + Mouse
Accessories Optional	Yes
Audio Inputs	1 Channel
Backup Device	USB x 2
Broadband Internet Access	Yes - Webserver with P2P Cloud - No Router Setup Needed
Call Monitor Output	BNC
Camera Input	8 on BNC + 8 IP Cameras through a router
Compression Method	255 × 233 × 42 ( W × D × H )
Dimensions	255 × 233 × 42 ( W × D × H )

Dome & PTZ Controls	Yes
Dual Streaming	Yes
Event Backup	USB
Event List	Yes
Hard Drive Options	1TB / 2TB / 3TB / 4TB / 6TB
Image Quality	5 Options of Picture KB Size up to 8MP
Main Monitor Output	1 HDMI, 1 VGA, 1 BNC
Model	FV-PRO-DVR2108-4K
Motion Detection	Yes
Network Access (LAN)	Yes
Password Control	Yes
Playback Speed	up to x 32
Power	DC12V from AC100-240V Adaptor
Privacy	Yes
RS485 Interface	Yes
Recording Modules	24hr / Schedule / Motion \ Alarm
Recording Resolution (Quality Settings)	6 Levels
Remote Interface	RS485
Resolution (Best)	8MP, 5MP, 4MP, 3MP, 1080P, 720P, WD1
Storage Media & Capacity	Up to 6TB
Time and Date	IP or P2Pfor no router set-up requirements using Cloud Server, Webserver - CMS
Transmission / Networking	IP or P2Pfor no router set-up requirements using Cloud Server, Webserver - CMS
Zoom	Yes