

PRODUCT



FV-PRO 9554E2A - 5 Megapixel 2.8mm Real Time H.265 IP Mini Eyeball with IR LED, WDR, Multi Stream, POE

Features

5MP (2592 × 1944) H.265 full real time coding

Max.resolution: 2592 × 1944

ICR auto switch, true day / night

20 ~ 30m IR night view distance

3D DNR, true WDR, HLC, BLC, Smart IR and ROI coding

One CVBS output; One MIC IN and one built-in MIC

Built-in micro SD card slot, up to 128GB

DC12V/PoE power supply

Supports smart phone, iPad, remote monitoring

IP67 ingress protection

Support three streams

P2P function optional

Supports face detection

Smart analytics : object removal detection, abnormal video signal detection, line crossing detection, region intrusion detection, people intrusion detection, people counting detection and crowd density detection

DETAILS

ADDITIONAL INFORMATION

Audio Inputs	MIC IN × 1; built-in MIC × 1
BLC	Yes
BLC/SSDR (WDR)	120dB
Compression Method	H.265
DNR	3D DNR
Dimensions	Φ 94.6 × 82.8
Image Sensor (CCD)	1 / 2.5 "CMOS
Lens	2.8 mm @F1.85, horizontal field of view: 101°
Lens Mount	M12
Main Monitor Output	4K, 1080P, VGA
Minimum Illumination - Colour	0.013 lux @ F1.2
Minimum Illumination - Mono	0 lux with IR

Operating Temperature	-30 °C ~ 60 °C (-22°F~140°F),Humidity: less than 95 % (non-condensing)
POE	Yes
Power Consumption	< 6W
Power Source	DC12V/PoE
Resolution (Best)	5MP 2592×1944
Shutter	Electronic Shutter 1 / 25 s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 128GB
Weight(Cameras)	Approx. 0.46KG
Within Range of IR LEDs	20 ~ 30 m